


Ultra V

HALF-CELL BIFACIAL MODULE

TYPE: STPXXXS-C72/Pmh+



545-565W **21.9%**
POWER OUTPUT MAX EFFICIENCY



Compatible with mainstream trackers

The module design is highly compatible with power plant tracking systems, which offers a cost-effective solution for large power plants



Anti-PID guarantee

Through the optimization of cell technology and material, the decay caused by PID phenomenon is reduced



Double-sided power generation

The gain of double-sided power generation increases up to max. 25% with the light on the back side, and significantly reduce LCOE



Extended wind and snow load tests

Module certified to withstand extreme wind (2400 Pascal) and snow loads (5400 Pascal)*




ISO 14001 Environment Management System
ISO 45001 Occupational Health and Safety
ISO 9001 Quality Management System
SA 8000 Social Responsibility Standards
IEC TS 62941 Guideline for Module Design

IEC 61730-2 (UL790) fire class C



30 years of linear warranty
15 years of product warranty



* Please refer to Suntech Standard Module Installation Manual for details.

*** WEEE only for EU market.

** Please refer to Suntech Limited Warranty for details.


**** Suntech reserves the right to the final.

Ultra V STPXXXS-C72/Pmh+ 545-565W

Mechanical Characteristics

Solar Cell	Monocrystalline silicon 182 mm
No. of Cells	144 (6 × 24)
Dimensions	2278 × 1134 × 30 mm (89.7 × 44.6 × 1.2 inches)
Weight	32.0 kg (70.5 lbs.)
Front \ Back Glass	2.0+2.0 mm (0.079+ 0.079inches) semi-tempered glass
Output Cables	4.0 mm ² , (-) 350 mm and (+) 160 mm in length or customized length
Junction Box	IP68 rated (3 bypass diodes)
Operating Module Temperature	-40 °C to +85 °C
Maximum System Voltage	1500 V DC (IEC)
Connectors	Wuxi Suntech STP-XC4-4 (Default)/ Staubli PV-KST4-EVO2A/xy (Optional)
Maximum Series Fuse Rating	25 A
Power Tolerance	0/+5 W
Frame	Anodized aluminum alloy frame
Packing Configuration	36 Pieces per pallet 720 Pieces per container /40'HC 2310×1120×1255mm 1202kg

For tracker installation, please turn to Suntech for mechanical load information.



Electrical Characteristics

Module Type	STP565S-C72/Pmh+		STP560S-C72/Pmh+		STP555S-C72/Pmh+		STP550S-C72/Pmh+		STP545S-C72/Pmh+	
Testing Condition	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT
Maximum Power (Pmax/W)	565	429	560	425	555	421	550	418	545	414
Optimum Operating Voltage (Vmp/V)	42.58	39.40	42.40	39.20	42.24	39.00	42.05	38.90	41.87	38.70
Optimum Operating Current (Imp/A)	13.27	10.90	13.21	10.85	13.14	10.80	13.08	10.75	13.02	10.71
Open Circuit Voltage (Voc/V)	50.41	47.50	50.23	47.40	50.07	47.20	49.88	47.00	49.69	46.90
Short Circuit Current (Isc/A)	14.20	11.46	14.14	11.41	14.07	11.35	14.01	11.30	13.96	11.26
Module Efficiency (%)	21.9		21.7		21.5		21.3		21.1	

STC: Irradiance 1000 W/m², module temperature 25 °C, AM=1.5; NMOT: Irradiance 800 W/m², ambient temperature 20 °C, AM=1.5, wind speed 1 m/s; Measuring tolerance of Pmax, Voc, Isc is within +/- 3%;

Specifications BNPI

Maximum Power (Pmax/W)	618	613	607	602	597
Short Circuit Current (Isc/A)	15.54	15.48	15.40	15.33	15.28
Open Circuit Voltage (Voc/V)	50.65	50.47	50.31	50.12	49.92

BNPI: Irradiance frontside 1000 W/m², backside 135 W/m², module temperature 25 °C, AM=1.5; Bifaciality coefficient (±5%): φPmax=70%, φVoc=99%, φIsc=70%.

Bifacial Gain with 5%

Maximum Power (Pmax/W)	593	588	583	578	572
Optimum Operating Voltage (Vmp/V)	42.58	42.40	42.24	42.05	41.87
Optimum Operating Current (Imp/A)	13.93	13.87	13.80	13.73	13.67
Short Circuit Current (Isc/A)	14.91	14.85	14.77	14.71	14.66
Open Circuit Voltage (Voc/V)	50.41	50.23	50.07	49.88	49.69


The bifacial gain is the additional gain from the back side of PV. It depends on the mounting method, orientation, tilt angle of the PV module and the albedo of the ground.

Temperature Characteristics

Nominal Module Operating Temperature (NMOT)	42 ± 2 °C
Temperature Coefficient of Pmax	-0.34%/°C
Temperature Coefficient of Voc	-0.26%/°C
Temperature Coefficient of Isc	+0.050%/°C

Graphs

Current-Voltage & Power-Voltage (555W)



Information on how to install and operate this product is available in the installation instruction. All values indicated in this data sheet are subject to change without prior announcement. The specifications may vary slightly. All specifications are in accordance with standard EN 50380. Color differences of the modules relative to the figures as well as discolorations of/in the modules which do not impair their proper functioning are possible and do not constitute a deviation from the specification.